

Flush Mount Pop-Out Dual Drink Holder

#43043

The guts of this slick unit come directly from the factory. We've imported them and designed a billet faceplate and mounting tray. Mount our included tray behind your dash and just slide the dual drink holder in. Mount it in your dash, or under; build it into a bench seat or even a center console.

You will need a spot that's $7\frac{1}{2}$ " wide and $1\frac{1}{4}$ " tall and is $5\frac{1}{4}$ " deep.

Thank you for buying a Streetworks product. Be confident that it will provide the quality and performance that you demand for your car. *Please read and understand ALL installation instructions before beginning.* Planning and preparation will make the actual installation process easy and quick.

1. You will need a mounting area of $7\frac{1}{2}$ " by $1\frac{1}{8}$ " approximately, or it may be installed below the dash. Make sure you have enough room behind the mounting area to allow the $5\frac{1}{4}$ " needed. You will also need to allow room for your brackets to mount this all to.
2. You will need to make a bracket for the cup holder mounting tray. The 2 holes closest to the front will need to be approximately $1\frac{1}{2}$ " from the face, and $7\frac{1}{8}$ " apart. The two rear holes will need to be approximately $3\frac{5}{8}$ " back from the front, $7\frac{1}{8}$ " apart. We recommend making the holes slotted front to rear, for adjustment.
3. If your angle is slightly off, you can use washers to shim.

